

XG3-ER Specifications



TECHNICAL

Operating System	Microsoft® Windows® Embedded Handheld 6.5
Processor	ARM Cortex-A8 CPU @1GHz
Memory	512MB RAM/1GB ROM
Expansion	User-accessible microSD card slot
Power	5200mAh rechargeable and hot-swappable Li-ion battery

PHYSICAL

Dimensions	7.4" H x 3.1" W x 8.3" L / 188mm H x 79mm W x 211mm L
Weight	21.7oz / 643.5g including battery
Keypad	34-Key Numeric; 57-Key Alpha-Numeric
Display	3.5" Color TFT VGA; 600 NITS
Touch Panel	Resistive touch screen

ENVIRONMENTAL

Operating Temperature	-4° to 140°F / -20° to 60°C
Storage Temperature	-40° to 158°F / -40° to 70°C
Humidity	95% RH (no condensation)
Drop	Multiple 6ft / 1.8m drops to concrete on all sides across a wide temperature range
Water & Dust	IP65
Electro Static Discharge (ESD)	+/- 15kVdc air; +/- 8kVdc contact

INTERFACE FEATURES

Communication Port	USB 2.0
Audio	Speaker; Microphone; 3.5mm headset jack; Supports VoIP
Alerts	Vibration; LED indicators; audio beep
LED Indicators	Tri-color indicators at top, rear and bottom
Scan Triggers	Pistol-grip trigger (located on handle, side and top)

DATA CAPTURE

Imager	Intermec EX25 Near/Far 2D Imager
Scanning Performance	Capable of scanning 1D and 2D barcodes from 6 in to 50 ft (5.2 cm to 15.2 m)

WIRELESS COMMUNICATION

WLAN	802.11a/b/g/n
Security	Authentication: EAP (TLS, PEAP-MSCHAPv2, PEAP-GTC, PEAP-TLS, TTLS, EAP-FAST, LEAP) Encryption: WPA2 (AES-CCMP), WPA (TKIP), WEP
WPAN	Bluetooth v2.1 with EDR

MOBILE APPURTENANCES

Motion Sensor	Accelerometer
---------------	---------------

ACCESSORIES

	Single-slot USB cradle kit	Four-slot charge only cradle kit
	Single-slot Ethernet cradle Kit	Four-slot battery charger
	Forklift cradle kit	Vehicle Mount cradle kit

Safety/Regulatory

Safety	CSA C22.2 No.60950-1-03; UL60950; EN60950-1; EN60825
EMI	FCC Part 15B
RF	FCC Part 15B and 15C, RSS-210, ICES-003
Hazardous Locations	UL Listing (US and Canada) Class I Div 2, Groups A, B, C, D