

XM60+ Specifications



TECHNICAL

Operating System	Microsoft Windows CE 5.0
Processor	Freescale™ i.MX31 @533MHz
Memory	128MB DDR SDRAM, 128MB NAND
Expansion	User accessible microSD card slot
Power	Swappable 3.7V 2000mAh rechargeable Li-ion battery

PHYSICAL

Dimensions	1.20" H x 3.11" W x 5.75" L / 30.5mm H x 79mm W x 146mm L
Weight	9.85oz / 279g with battery
Keypad	Backlit numeric keypad or backlit PDA keypad (with 4-way navigation)
Display	3.5" Color TFT QVGA (240x320); 262K colors
Touch Panel	Analog resistance type; stylus input

ENVIRONMENTAL

Operating Temperature	14° to 122° F / -10° to 50° C
Storage Temperature	-13° to 158° F / -25° to 70° C
Humidity	5% to 90% RH (no condensation)
Drop	Multiple 4ft / 1.2m drops to concrete on all sides across a wide temperature range
Water & Dust	IP54 Category II
Vibration	0.03 G ² /Hz from 20Hz to 2kHz; 1 hour random wave per axis
Electro Static Discharge (ESD)	+/- 15kVDC air; +/- 8kVDC contact
Sterilization	76.9% to 81.4% concentration alcohol rub
Ambient Light	450ft-candelas (artificial light); 8,000ft-candelas (sunlight)

INTERFACE FEATURES

Audio	Speaker and Microphone
Alerts	Vibration, LED indicators, audio beep
LED Indicators	Tri-color
Scan Triggers	Left, right, center buttons

DATA CAPTURE

Imager	1D/2D Adaptus® Imaging Technology; 752 x 480 pixel CMOS area imager
1D Symbologies	China Post, Codabar, Codablock F, Code 11, Code 16K, Code 32 Pharmaceutical (PARAF), Code 39, Code 49, Code 93 and 93i, Code 128, EAN-8, EAN-13, Interleaved 2 of 5, ISBT 128, Matrix 2 of 5, Korea Post, MSI, Plessey Code, PosiCode, Reduced Space Symbology (RSS-144, RSS Limited, RSS Expanded), Straight 2 of 5 IATA (two-bar start/stop), Straight 2 of 5 Industrial (three-bar start/stop), Telepen, Trioptic Code, UPC-A, UPC-A with Extended Coupon Code, UPC-E, UPC-E1
2D Symbologies	PDF417 (EAN-UCC Composite, MicroPDF417, PDF417, TCIF Linked Code 39, TLC39), 4-CB (4-State Customer Barcode), Australian Post, Aztec Code, Aztec Mesas, British Post, Canadian Post, Data Matrix, ID-tag (UPU 4-State), Japanese Post, KIX (Netherlands) Post, MaxiCode, OCR, Planet Code, Postnet, QR Code

DATA COMMUNICATION

IrDA	Standard v1.2
USB	Hi-Speed USB 2.0 (up to 480mbps)
WPAN	Bluetooth v1.2
WLAN	Optional Summit IEEE 802.11b/g or 802.11a/b/g; Cisco CCX v4 certified
Wireless Security	Authentication: EAP (TLS, PEAP-MSCHAPv2, PEAP-GTC, PEAP-TLS, TTLS, EAP-FAST, LEAP) or PSK Encryption: WPA2 (AES-CCMP), WPA (TKIP), WEP - 40 bit and 128-bit keys

ACCESSORIES

Single-Slot Cradle Kit	RFID Reader	Stylus 5-Pack
Four-Slot Cradle Kit	Cable Cup	Stylus Tether
Modem Cradle Kit	Vehicle Charger	Nylon Holster
Extended Capacity Battery	Syncing/Charging Cables	Adjustable Handstrap
Magnetic Stripe Reader	Battery Charger	Operating Case

SAFETY/REGULATORY

Safety	CSA C22.2 No. 60950-1-03, EN60950-1:2001+A11
EMI	FCC Part 15 Subpart B, EN55022:1998+A1:2000+A2:2003, EN55024:1998+A1:2000+A2:2003, ICES-003 Issue 4, AS/NZS CISPR 22:2004
RF	FCC Part 15 Subpart C and Subpart B, EN300 328 v1.6.1 (2004-11), EN301 489-1 v1.6.1 (2005-09), EN301 489-17 v1.2.1 (2002-08), RSS 210 Issue 6
Hazardous Locations	UL Listing (US and Canada) Class 1, Division 2, Groups A, B, C, D