

XG200 Specifications

TECHNICAL

Operating System	Android 7
Processor	1.2 GHz Qualcomm Snapdragon™ 410 quad-core
Memory	2GB/16GB
Power	6300mAh 3.63v rechargeable Li-ion battery

PHYSICAL

Dimension	8.05" x 3.11" x 6.88" 204.55mm L x 79mm W x 175mm D
Weight	20.67oz / 586g including battery
Keypad	24-Key Numeric or 51-Key Alpha-Numeric
Display	4.3" WVGA (480 x 800 pixel) with Corning Gorilla Glass 3
Touch Panel	Multi-touch capacitive touch screen

ENVIRONMENTAL

Operating Temperature	-4° to 140° F / -20° to 60° C
Storage Temperature	-13° to 158° F / -25° to 70° C
Humidity	Non-condensing, 95%
Drop	Multiple 5ft / 1.5m drops to concrete at operating temperature; Multiple 6ft / 1.8m drops to concrete at ambient temperature per MIL-STD-810G
Water & Dust	IP65
Tumble	500 tumbles, 3.3ft / 1.0m
Electro Static Discharge (ESD)	+/- 15kV air; +/- 8kV contact

INTERFACE FEATURES

Audio	Speaker
Alerts	Vibration; LED indicators
Connectors	USB Type C v. 2.0
LED Indicators	Dual-color
Motion Sensor	Accelerometer

DATA CAPTURE

Imager	Honeywell N6603ER 2D Imager or Honeywell EX25 near/far imager
--------	---

NETWORK COMMUNICATION

WLAN	802.11a/b/g/n/d/h/i/k/r/v
Security	IEEE802.11; WEP; WPA/WPA2 Personal; WPA/WPA2 Enterprise; RC4 Algorithm / TKIP; RC4 Algorithm / AES, Rijndael Algorithm; EAP-FAST; EAP-TLS; EAP-TTLS; PEAP-GTC; PEAP-MSCHAPv2; PEAP-TLS; LEAP; CCX v4 supported
WPAN	Bluetooth Class 1, v4.1

ACCESSORIES

	Single-Slot USB Cradle Kit
	Single-Slot Ethernet Cradle Kit
	Spare Battery
	Six-Slot Battery Charger

SAFETY/REGULATORY

Safety	IEC 60950; EMC; RF; SAR; LED; Laser
Radio	FCC; IC; CE
Environmental	RoHS and WEEE compliant



Janam Technologies
100 Crossways Park West
Suite 105
Woodbury, NY 11797

Phone: +1.877.JANAM.99
Local: +1.516.677.9500
Fax: +1.516.320.8031
Email: inquiries@janam.com

Contact Technical Support:
NA: +1.866.915.5311
EMEA: +44.1202.946945
Email: janamcare@janam.com